



1-110 Quarter-Turn Pr20.1 L30-60



Advantages

- Extended Quarter-turns for cutout Pr20.1.
- IP65/67 according to DIN EN 60529 by sealing kit (optional).
- RH / LH application.
- Grounding by grounding nut.
- On request parts can be assembled.
- The Quarter-turn can be screwed into the cutout with the pre-assembled cam.

Materials

- **Housing:** zinc die, chrome plated or black
- **Nuts:** steel, zinc plated
- **Grounding nut and adapter:** zinc die, untreated

Remarks

(S) Door-thickness see table
Please configure the Quarter-turn with insert (adapter) and cam.
Negatively bent cams can not be installed pre-assembled.
By using inserts the adapter is optional, by using knobs the adapter is necessary.
1. nut
2. grounding nut



Quarter-Turn housing, zinc die, chrome plated + nut

	Part Number	Housing length	Door-thickness (S)	suitable Adapter set	Grounding type	Installation type	Delivery Unit
a)	200-9011.00-00000	30 mm	max. 20 mm	L20		screw-on	10 pcs.
a)	200-9012.00-00000	30 mm	max. 20 mm	L20	Grounding nut	screw-on	10 pcs.
a)	200-9015.00-00000	36 mm	max. 26 mm	L26		screw-on	10 pcs.
a)	200-9016.00-00000	36 mm	max. 26 mm	L26	Grounding nut	screw-on	10 pcs.
a)	200-9019.00-00000	40 mm	max. 30 mm	L30		screw-on	10 pcs.
a)	200-9020.00-00000	40 mm	max. 30 mm	L30	Grounding nut	screw-on	10 pcs.
a)	200-9023.00-00000	50 mm	max. 40 mm	L40		screw-on	10 pcs.
a)	200-9024.00-00000	50 mm	max. 40 mm	L40	Grounding nut	screw-on	10 pcs.
a)	200-9027.00-00000	60 mm	max. 50 mm	L50		screw-on	10 pcs.
a)	200-9028.00-00000	60 mm	max. 50 mm	L50	Grounding nut	screw-on	10 pcs.

Quarter-Turn housing, zinc die, black + nut

	Part Number	Housing length	Door-thickness (S)	suitable Adapter set	Grounding type	Installation type	Delivery Unit
a)	200-9013.00-00000	30 mm	max. 20 mm	L20		screw-on	10 pcs.
a)	200-9014.00-00000	30 mm	max. 20 mm	L20	Grounding nut	screw-on	10 pcs.
a)	200-9017.00-00000	36 mm	max. 26 mm	L26		screw-on	10 pcs.
a)	200-9018.00-00000	36 mm	max. 26 mm	L26	Grounding nut	screw-on	10 pcs.
a)	200-9021.00-00000	40 mm	max. 30 mm	L30		screw-on	10 pcs.
a)	200-9022.00-00000	40 mm	max. 30 mm	L30	Grounding nut	screw-on	10 pcs.
a)	200-9025.00-00000	50 mm	max. 40 mm	L40		screw-on	10 pcs.
a)	200-9026.00-00000	50 mm	max. 40 mm	L40	Grounding nut	screw-on	10 pcs.
a)	200-9029.00-00000	60 mm	max. 50 mm	L50		screw-on	10 pcs.
a)	200-9030.00-00000	60 mm	max. 50 mm	L50	Grounding nut	screw-on	10 pcs.



Function extension

- e) 209-9006.00-00000 **Sealing kit IP65/IP67 for Quarter-Turns Pr20.1 L30-60**



Assembly options

- 200-0003.00-00000 **Assembling adapter without o-ring**
- 200-0033.00-00000 **Assembling cam 90° to handle with o-ring**
- 200-0004.00-00000 **Assembling adapter, with o-ring**
- 200-0019.00-00000 **Assembling cam 90° to handle without o-ring**



Accessories

- d1) 1-264 **Slam-Cam**
- d1) 1-262 **Cams variable**
- d1) 1-260 **Hooked Cam**
- d) 1-102 **Cams L35/45 Steel**
 - 1-115 **Handles for Quarter-Turns Pr20.1**
 - 1-270 **Dust Caps and Sealing Plug Pr20.1**
- b) 1-101 **Inserts Pr20.1**
 - 1-275 **Emergency Handle + Anti-Rotation Device Pr20.1**
 - 1-270.01 **Finger Pull for Quarter-Turn Pr20.1**
- 6-100 **Wrench**
- c) 200-9031.00-00000 **Adapter set L20**
- c) 200-9033.00-00000 **Adapter set L30**
- c) 200-9034.00-00000 **Adapter set L40**
- c) 200-9035.00-00000 **Adapter set L50**
- c) 200-9032.00-00000 **Adapter set L26**
- 6-101 **Universal Key**

