

Flush Quarter-Turn L22-66

1-112



Advantages

- Flush-mounted quarter-turn for cutout Ø22mm.
- With the PA nut M22 x 1.5mm, the housing is put exactly into position and secured with the anti-rotation device. Precise detent for optimized alignment.
- In conjunction with the stop plate, stop less constructions with aluminum profiles and/or with flat components can be latched perfectly.
- Vibration-proof according to DIN EN 61373.
- RH / LH application.

Material

- **Housing:** zinc die, chrome plated or black
- **Nut:** PA
- **Anti-rotation device:** zinc die, zinc plated

Remarks

(S) Door-thickness see table

Minimum door-thickness 5mm

d) adapter set

e) stop plate

Please configure the quarter-turn with insert, (adapter) and cam.

By using inserts the adapter is optional, by using knobs the adapter is necessary.

Quarter-Turn housing, zinc die

	Product number	Surface	Housing length	Door-thickness (S)	suitable Adapter set	Installation type	Delivery Unit
a)	200-9089.00-00000	black	22 mm	0 mm - 7 mm	-	screw-on	10 pcs.
a)	200-9088.00-00000	chrome plated	22 mm	0 mm - 7 mm	-	screw-on	10 pcs.
a)	200-9090.00-00000	chrome plated	36 mm	0 mm - 21 mm	L20	screw-on	10 pcs.
a)	200-9092.00-00000	chrome plated	42 mm	0 mm - 27 mm	L26	screw-on	10 pcs.

	Product number	Surface	Housing length	Door-thickness (S)	suitable Adapter set	Installation type	Delivery Unit
a)	200-9094.00-00000	chrome plated	46 mm	0 mm - 31 mm	L30	screw-on	10 pcs.
a)	200-9096.00-00000	chrome plated	56 mm	0 mm - 41 mm	L40	screw-on	10 pcs.
a)	200-9098.00-00000	chrome plated	66 mm	0 mm - 51 mm	L50	screw-on	10 pcs.

