



# 1-120 Cylinder Quarter-Turn Pr20.1 L18



## Advantages

- Cylinder quarter-turn for cutout Pr20.1.
- IP65 according to DIN EN 60529 by dust cap 200-4101 (optional).
- IP65/IP67 according to DIN EN 60529 by dust cap 200-4103 (optional).
- RH / LH application.
- Grounding by grounding nut.
- Completely pre-assembled **without** cam.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- 2 keys included.
- With stainless steel cylinder cover and dust-shutter.

## Materials

- **Housing:** zinc die, chrome plated or black
- **Grounding nut:** stainless steel

## Remarks

(S) Door-thickness max. 8mm  
Please configure the quarter-turn with a cam.  
Maximum load for the key 4Nm.



## Cylinder Quarter-turn, zinc die

	Part Number	Head diameter	Latching type	Surface	Grounding type	Installation type	Delivery Unit
a)	200-9201.00-00000	Ø28	keyed alike DIRAK 1333	chrome plated	Grounding nut	screw-on	1 pcs.
a)	500-9201.00-00000	Ø28	keyed alike DS200	chrome plated	Grounding nut	screw-on	1 pcs.
a)	200-9203.00-00000	Ø28	keyed different	chrome plated	Grounding nut	screw-on	1 pcs.
a)	200-9202.00-00000	Ø28	keyed alike DIRAK 1333	black	Grounding nut	screw-on	1 pcs.
a)	500-9202.00-00000	Ø28	keyed alike DS200	black	Grounding nut	screw-on	1 pcs.
a)	200-9204.00-00000	Ø28	keyed different	black	Grounding nut	screw-on	1 pcs.
a)	200-9205.00-00000	Ø32	keyed alike DIRAK 1333	chrome plated	Grounding nut	screw-on	1 pcs.
a)	500-9205.00-00000	Ø32	keyed alike DS200	chrome plated	Grounding nut	screw-on	1 pcs.
a)	200-9207.00-00000	Ø32	keyed different	chrome plated	Grounding nut	screw-on	1 pcs.
a)	200-9206.00-00000	Ø32	keyed alike DIRAK 1333	black	Grounding nut	screw-on	1 pcs.
a)	500-9206.00-00000	Ø32	keyed alike DS200	black	Grounding nut	screw-on	1 pcs.
a)	200-9208.00-00000	Ø32	keyed different	black	Grounding nut	screw-on	1 pcs.



### Assembly options

200-0001.00-00000 **Assembling cam without o-ring**



### Accessories

- b) 1-270.01 **Finger Pull for Quarter-Turn Pr20.1**
- d) 1-102 **Cams L35/45 Steel**
- d) 1-262 **Cams variable**
- c) 200-4101.00-00000 **Dust cap**
- c) 200-4103.00-00000 **Dust cap**

