



1-121 Cylinder Quarter-Turn Polyamide Pr20.1 L18



Advantages

- Polyamide cylinder quarter-turn for cutout Pr20.1.
- Protective insulated and vibration-proof.
- IP65 according to DIN EN 60529 by dust cap 200-4101 (optional).
- IP65/67 according to DIN EN 60529 by dust cap 200-4103 (optional).
- RH / LH application.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- 2 keys included in scope of delivery.

Materials

- **Housing and finger pull:** PA, black

Remarks

(S) Door-thickness max. 8mm
Completely pre-assembled without cam.



Cylinder Quarter-turn

	Part Number	Latching type	Material nut	Surface nut	Installation type	Delivery Unit
a)	200-9210.00-00000	keyed alike DIRAK 1333	PA	black	screw-on	1 pcs.
a)	200-9211.00-00000	keyed alike DIRAK 1333	steel	zinc plated	screw-on	1 pcs.
a)	200-9212.00-00000	keyed alike DIRAK 1333	stainless steel		screw-on	1 pcs.
a)	200-9213.00-00000	keyed different	PA	black	screw-on	1 pcs.
a)	200-9214.00-00000	keyed different	steel	zinc plated	screw-on	1 pcs.
a)	200-9215.00-00000	keyed different	stainless steel		screw-on	1 pcs.



Function extension

200-4103.00-00000 **Dust cap**

200-4101.00-00000 **Dust cap**



Assembly options

200-0001.00-00000 **Assembling cam without o-ring**



Accessories

- d) 1-270.01 **Finger Pull for Quarter-Turn Pr20.1**
- c) 1-260 **Hooked Cam**
- c) 1-102 **Cams L35/45 Steel**
- b) 200-5320.00-00000 **PA cam, L35mm / H20mm**
- b) 200-5322.00-00000 **PA cam, L35mm / H22mm**
- b) 200-5325.00-00000 **PA cam, L35mm / H25mm**
- b) 200-5328.00-00000 **PA cam, L35mm / H28mm**
- b) 200-5318.00-00000 **PA cam, L35mm / H18mm**

