



1-160 Flush-Mounted Quarter-Turn L20

RoHS
WEEE

Advantages

- Flush-mounted version.
- Quarter-turn screw-on, weld-on or rivet-on.
- RH and LH version.
- This quarter-turn consists of three basic parts which can be combined to suit your application.

Materials

- **Housing:** steel, zinc plated
- **Bezel:** zinc die, untreated

Remarks

Door-thickness min. 1.5mm



Quarter-Turn housing with bezel

	Part Number	Version	Housing length	Installation type	Delivery Unit
a)	200-9036.00-00000	RH version	20 mm	screw-/ weld-on/ rivet	10 pcs.
a)	200-9037.00-00000	LH version	20 mm	screw-/ weld-on/ rivet	10 pcs.

Quarter-Turn housing with bezel, flush

Part Number	Version	Housing length	Installation type	Delivery Unit	
b)	100-9010.00-00000	RH version	20 mm	screw-/ weld-on/ rivet	10 pcs.
b)	100-9011.00-00000	LH version	20 mm	screw-/ weld-on/ rivet	10 pcs.

Assembly options

200-0001.00-00000 **Assembling cam without o-ring**

Accessories

- c) 1-101 **Inserts Pr20.1**
- d) 1-102 **Cams L35/45 Steel**
- d) 1-262 **Cams variable**
- 6-100 **Wrench**
- 6-101 **Universal Key**

