



1-210 Quarter-Turn with Conical Square Insert Pr20.1 L18



Advantages

- Quarter-turn with conical square insert, operated by a "Bern" key.
- IP65 according to DIN EN 60529 by sealing kit (optional).
- RH / LH application.
- This quarter-turn consists of three basic parts which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled quarter-turn can be installed in the cutout.

Materials

- **Housing:** zinc die, chrome plated or black
- **Nut:** steel, zinc plated
- **Insert:** steel, zinc plated, or zinc die, chrome plated

Remarks

(S) Door-thickness max. 8mm
On request parts can be assembled by DIRAK.



Quarter-Turn housing, zinc die

	Part Number	Surface	Housing length	Installation type	Delivery Unit
a)	200-9065.00-00000	chrome plated	18 mm	screw-on	10 pcs.
a)	200-9086.00-00000	black	18 mm	screw-on	10 pcs.

Inserts

	Part Number	Insert	Material	Surface	Delivery Unit
b)	200-9138.00-00000	Conical square 9mm	zinc die	chrome plated	10 pcs.
b)	200-9175.00-00000	Conical square 9mm	steel	zinc plated	10 pcs.
b)	200-9183.00-00000	Conical square 9mm	steel	chrome plated	10 pcs.

+ Function extension

- d) 209-9002.00-00000 **Sealing kit IP65 for Quarter-Turns Pr20.1**

Assembly options

- 200-0002.00-00000 **Assembling cam with o-ring**
- 200-0001.00-00000 **Assembling cam without o-ring**

* Accessories

- c) 1-102 **Cams L35/45 Steel**
- c) 1-262 **Cams variable**
- 6-105 **Keys for the Railway Sector**

