



1-211 Quarter-Turn with Conical Square Insert Pr20.1 L18



Advantages

- Quarter-turn with housing length 18mm.
- IP65 according to DIN EN 60529.
- RH / LH application.

Materials

Housing: steel, chrome plated or zinc die, chrome plated
Nut. insert: steel, zinc plated
O-ring and flat sealing: NBR/Perbunan

Remarks

(S) Door-thickness max. 8mm
Pre-assembled with insert but without cam.
1. flat external seal
2. conical square insert
3. o-ring 12x2



Quarter-Turn with insert

	Part Number	Material	Insert	Head diameter	Housing length	Delivery Unit
a)	200-8092.00-00000	steel	Conical square 9mm	Ø28	18 mm	10 pcs.
b)	200-9079.00-00000	zinc die	Conical square 9mm	Ø28	18 mm	10 pcs.
c)	200-8219.00-00000	steel	Conical square 9mm	Ø32	18 mm	10 pcs.

* Accessories

d) 1-102 Cams L35/45 Steel

d) 7-105 Cams L35/45 Stainless Steel

- 7-105 Cams L53/45 Stainless Steel
- d) 1-260 Hooked Cam
- d) 1-261 Cams with Ramp
- d) 1-262 Cams variable
- 6-105 Keys for the Railway Sector

