



2-040 Quarter-Turn PrA L16



Advantages

- Quarter-turn for cutout type A 50 x 25.
- IP65 according to DIN EN 60529 by sealing kit (optional).
- RH/ LH application.
- Grounding by grounding clip (optional).
- The quarter-turn consists of three component groups a), b) and c), their versions can be combined in any way.
- Pre-assembled deliverable on request.
- The quarter-turn can be installed pre-assembled.
- Pre-assembly of 3-point cam also possible.

Materials

- **Bearing plate:** zinc die, untreated
- **Escutcheons:** PA, black
- **Self tapping screw:** steel, zinc plated

Remarks

Height 16mm.
Min. A dimension = 8mm.
Escutcheon b2) only in use with insert double bit.
For door-thicknesses greater than 3.5mm longer screws for the installation are required.



Bearing plate and Escutcheons

	Part Number	Name	Material	Surface	Door-thickness (S)	Installation type	Delivery Unit
a)	207-2707.00-00016	Bearing plate 16mm	zinc die	untreated		screw-on	10 pcs.
b)	208-9306.00-00000	Escutcheon PrA	PA	black	1.3 - 3.5 mm	screw-on	1 pcs.
b1)	208-9307.00-00000	Escutcheon PrA SOFTLINE	PA	black	1.3 - 3.5 mm	screw-on	1 pcs.
b2)	208-9308.00-00000	Escutcheon for double bit PrA	PA	black	1.3 - 3.5 mm	screw-on	1 pcs.

Function extension

- g) 3-011 Grounding Clip Stainless Steel
- e)- f) 209-9007.00-00000 Sealing kit IP65 for Quarter-Turn PrA

* Accessories

- c) 1-101 Inserts Pr20.1
- d) 1-102 Cams L35/45 Steel
- d1) 2-151.04 3-Point Cam Adapter
- 6-100 Wrench
- 6-101 Universal Key

