



## 4-152DST DST Hinge Pr05 180°



### Advantages

- For surface mounted doors for single cabinets.
- Hinge partly visible.
- Door bending 20mm.
- RH / LH application.
- 180° Opening angle.
- Lift-off.
- Installation of the frame-part by simple tool-less push into the cutout.
- IP65 according to DIN EN 60529 (optional).

### Materials

- **Frame- and door-part:** zinc die, matte black
- **Pin:** steel, zinc plated, AISI 304 or POM
- **Snap wedges:** sintered steel, zinc plated

### Remarks

For light applications only!



## Hinge

	Part Number	Clamping range (S)	Material pin	Pin version	Pin length L	Installation type	Delivery Unit
a)	412-9059.00-01217	1.2 - 1.7 mm	steel, zinc plated	loose	43 mm	tool-less	10 pcs.
a)	412-9059.00-01722	1.7 - 2.2 mm	steel, zinc plated	loose	43 mm	tool-less	10 pcs.
b)	412-9060.00-01217	1.2 - 1.7 mm	AISI 304	loose	43 mm	tool-less	10 pcs.
b)	412-9060.00-01722	1.7 - 2.2 mm	AISI 304	loose	43 mm	tool-less	10 pcs.
c)	412-9061.00-01217	1.2 - 1.7 mm	POM	self-locking	57 mm	tool-less	10 pcs.
c)	412-9061.00-01722	1.7 - 2.2 mm	POM	self-locking	57 mm	tool-less	10 pcs.

**+** Function extension

839-3770.40-02120 **O-ring 21 x 2.0mm**

**\*** Accessories

292-0403.06-07035 **Cutout-cover**

292-0403.06-09005 **Cutout-cover**

292-0306.80-02530 **Tool for uninstallation**

