

Quarter-Turn Pr14.1 L13.5 Stainless Steel

7-050



Advantages

- IP65 DIN EN 60529 by sealing kit (optional).
- Fire protection tested with E60 classification according to DIN EN 45545-3.
- RH / LH application.
- On request parts can be assembled by DIRAK.
- A pre-assembled quarter-turn can be installed in the cutout and combined with finger pull of product system 1-060.

Material

- **Housing and insert** : AISI 316
- **Screw, serrated washer**: AISI 304
- **Wave washer and cam**: AISI 301

Remarks

With assembled cam - door thickness (S) max. 2mm

With unassambled cam - door thickness (S) max. 5mm

When using finger pull (g) the H-dimension decreases by 0.8mm!

Please configure the quarter-turn with insert and cam.

Quarter-Turn housing + nut

	Product number	Housing length	Installation type	Delivery Unit
a)	220-9018.00-00000	13,5 mm	screw-on	1 pc.

Insert with screw, spring- and serrated washer

	Product number	Insert	Delivery Unit
c)	220-9120.00-00000	Square 6mm	1 pc.
d)	220-9121.00-00000	Triangular 6.5mm	1 pc.

	Product number	Insert	Delivery Unit
e)	220-9122.00-00000	Slotted 1,5x3mm	1 pc.

Cams L24, with stop

	Product number	H-dimension	Delivery Unit
b)	220-0503.04-00000	7,5 mm	1 pc.
b)	220-0501.04-00000	13,5 mm	1 pc.
b)	220-0502.04-00000	19,5 mm	1 pc.



