



7-080.03 Quarter-Turn with Conical Square Insert Pr20.1 L18-L50 Stainless Steel



Advantages

- Quarter-turn with housing length 18-50mm.
- IP65/IP67 according to DIN EN 60529.
- RH / LH application.
- Grounding by grounding nut.

Materials

Housing: AISI 316 or 303
Insert: AISI 303
O-ring and flat external seal: NBR
Nut, wave washer, adapter and serrated screw: stainless steel

Remarks

1. conical square, 9mm
 2. flat external seal
- Pre-assembled without cam



Quarter-Turn with insert

	Part Number	Material	Head diameter	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	200-9080.00-00018	AISI 316	Ø28	18 mm	max. 8 mm	screw-on	1 pcs.
b)	200-9080.00-00022	AISI 303	Ø28	22 mm	max. 12 mm	screw-on	1 pcs.
b)	200-9080.00-00030	AISI 303	Ø28	30 mm	max. 20 mm	screw-on	1 pcs.
b)	200-9080.00-00036	AISI 316	Ø28	36 mm	max. 26 mm	screw-on	1 pcs.
b)	200-9080.00-00040	AISI 316	Ø28	40 mm	max. 30 mm	screw-on	1 pcs.
b)	200-9080.00-00050	AISI 316	Ø28	50 mm	max. 40 mm	screw-on	1 pcs.
c)	100-9016.00-00018	AISI 303	Ø32	18 mm	max. 8 mm	screw-on	1 pcs.
d)	100-9016.00-00030	AISI 303	Ø32	30 mm	max. 20 mm	screw-on	1 pcs.
d)	100-9016.00-00036	AISI 303	Ø32	36 mm	max. 26 mm	screw-on	1 pcs.
d)	100-9016.00-00040	AISI 303	Ø32	40 mm	max. 30 mm	screw-on	1 pcs.
d)	100-9016.00-00050	AISI 303	Ø32	50 mm	max. 40 mm	screw-on	1 pcs.

* Accessories

- e) 7-105 Cams L35/45 Stainless Steel
- e) 1-260 Hooked Cam
- e) 1-261 Cams with Ramp
- 6-105 Keys for the Railway Sector

