



7-080 Quarter-Turn Pr20.1 L18 - L60 Stainless Steel



Advantages

- Housing L18 according to IP65 DIN EN 60529. It can reach IP67 DIN EN 60529 by additional o-ring (200-1002.00-00000).
- Housings L30 to L60 can reach IP65/67 DIN EN 60529 by additional o-ring (839-3771.00-00935).
- Adapter sets can consist of one or more separate extensions.
- A pre-assembled quarter-turn can be installed through the cutout.

Materials

- **Housing:** AISI 303 or AISI 316
- **Grounding nut and adapter:** AISI 316
- **O-ring and flat external seal:** NBR

Remarks

1. flat external seal
Please configure the quarter-turn with insert and cam.



Housing with flat external seal and single sided grounding nut

	Part Number	Housing length	Door-thickness (S)	suitable Adapter set	Material	Installation type	Delivery Unit
a)	200-9043.00-00000	18 mm	max. 8 mm		AISI 316	screw-on	1 pcs.
b)	200-9072.00-00000	30 mm	max. 20 mm	L14	AISI 303	screw-on	1 pcs.
b)	100-9024.00-00000	36 mm	max. 26 mm	L21	AISI 303	screw-on	1 pcs.
b)	200-9073.00-00000	40 mm	max. 30 mm	L25	AISI 303	screw-on	1 pcs.
b)	200-9074.00-00000	50 mm	max. 40 mm	L33	AISI 303	screw-on	1 pcs.
b)	200-9075.00-00000	60 mm	max. 50 mm	L44	AISI 303	screw-on	1 pcs.



Assembly options

200-0002.00-00000 **Assembling cam with o-ring**

200-0004.00-00000 **Assembling adapter, with o-ring**



Accessories

- c) 7-082 **Insert Stainless Steel Pr20.1**
- d) 7-105 **Cams L35/45 Stainless Steel**
- 6-100 **Wrench**
- 1-270.01 **Finger Pull for Quarter-Turn Pr20.1**
- 1-270 **Dust Caps and Sealing Plug Pr20.1**
- g) 100-9019.00-00000 **Adapter set L14**
- g) 100-9021.00-00000 **Adapter set L25**
- g) 100-9020.00-00000 **Adapter set L21**
- e) 200-1002.00-00000 **O-ring 10 x 2.0mm**
- g) 100-9023.00-00000 **Adapter set L44**
- g) 100-9022.00-00000 **Adapter set L33**
- f) 839-3771.00-00935 **O-ring 9 x 3.5mm**
- 6-101 **Universal Key**



