

Oil level indicators

with prismatic window, technopolymer

MATERIAL

Transparent polyamide based (PA-T) technopolymer. Avoid contact with alcohol or detergents containing alcohol. The window consists of a continuous series of prisms which provide a clear and immediate reading of the level of the oil contained in the reservoir.

PACKING RING

NBR synthetic rubber.

MAXIMUM CONTINUOUS WORKING TEMPERATURE

100°C.

TECHNICAL DATA

The tightening torque indicated in the table guarantees an optimal tightness, keeping the packing ring in the correct position.

NOTE


For use with other fluids with special additives, please contact ELESA Sales Department.

ACCESSORIES ON REQUEST

Brass nut type GH. (see page 1743) for fitting to reservoirs with wall thickness smaller than 5 mm.



ELESA Original design



Code	Description	dl	A	B	D	d	s	Tightening torque [Nm]	⚖️
13652	HFTX.9/PR-1/4	G 1/4	10	6	18	9	15	2+3	3
13672	HFTX.12/PR-3/8	G 3/8	7.5	7	22	11	19	3+5	4
13692	HFTX.15/PR-1/2	G 1/2	10.5	8	26	14	22	4+6	5
13722	HFTX.20/PR-3/4	G 3/4	10.5	9	31.5	20	27	6+8	8
13742	HFTX.24/PR-1	G 1	11	10	40	25	34	8+10	12

Oil level indicators

with prismatic window, technopolymer

MATERIAL

Transparent polyamide based (PA-T) technopolymer. Avoid contact with alcohol or detergents containing alcohol. The window consists of a continuous series of prisms which provide a clear and immediate reading of the level of the oil contained in the reservoir.

PACKING RING

NBR synthetic rubber

The positioning of the packing ring in its housing guarantees a high tightening torque.

MAXIMUM CONTINUOUS WORKING TEMPERATURE

100°C.

NOTE


For use with other fluids with special additives, please contact ELESA Sales Department.

ACCESSORIES ON REQUEST

Brass nut GH. (see page 1743) for fitting to reservoirs with wall thickness smaller than 5 mm.



ELESA Original design



Code	Description	dl	A	B	D	d	s	Tightening torque [Nm]	⚖️
14692	HFTR.15/PR-1/2	G 1/2	10.5	9	28	15	24	8+10	6
14722	HFTR.20/PR-3/4	G 3/4	10.5	10.5	35	20	32	10+12	9
14742	HFTR.24/PR-1	G 1	11	13.5	42.5	24	38	10+12	13
14762	HFTR.30/PR-1 1/4	G 1 1/4	19	16	52	30.5	41	12+14	21

