

## Hinges

detachable, for welding, Stainless Steel / Aluminium

### SPECIFICATION

#### Version in Stainless Steel

AISI 304 **NI**  
Pin / Washer  
Stainless Steel AISI 303

AISI 316 **A4**  
Pin / Washer  
Stainless Steel AISI 316

#### Version in Aluminium


weldable, 3.3206 **AL**  
Pin / Washer  
Stainless Steel AISI 303

### INFORMATION


Hinges GN 128.2 are produced from drawn weldable profiled Stainless Steel or Aluminium extrusions.  
The pin is fixed in the lower half.

### TECHNICAL INFORMATION

- Stainless Steel characteristics (see page A26)
- List of hinges types (see page I362)



Example of installation



#### GN 128.2-AL

Description	l	d1	d2	s1	s2	⚖
GN 128.2-60-AL	60	10	6	12	2	17
GN 128.2-80-AL	80	13	8	15.5	2	38
GN 128.2-100-AL	100	16	10	20	3	75
GN 128.2-120-AL	120	16	11	20	3	90
GN 128.2-150-AL	150	20	13	25.5	3	180
GN 128.2-180-AL	180	20	14	25.5	3	221

#### GN 128.2-A4

**STAINLESS STEEL**

Description	l	d1	d2	s1	s2	⚖
GN 128.2-80-A4	80	13	8	15.5	2	86
GN 128.2-100-A4	100	16	10	20	3	150
GN 128.2-120-A4	120	16	11	20	3	204

#### GN 128.2-NI

**STAINLESS STEEL**

Description	l	d1	d2	s1	s2	⚖
GN 128.2-60-NI	60	10	6	12	2	36
GN 128.2-80-NI	80	13	8	15.5	2	85
GN 128.2-100-NI	100	16	10	20	3	164
GN 128.2-120-NI	120	16	11	20	3	199
GN 128.2-150-NI	150	20	13	25.5	3	394
GN 128.2-180-NI	180	20	14	25.5	3	400

