

Retaining Magnets

Disk-Shaped, with Female Thread, with Rubber Jacket

SPECIFICATION

- Steel part
- Zinc plated
- Material of the magnet
NdFeB **ND**
Neodymium, iron, boron
Temperature resistant up to 80 °C
- Rubber jacket
Elastomer (TPE)
80 shore A ≈
Black **SW**
White **WS**

INFORMATION

The retaining magnets GN 51.5 with rubber jacket form a system together with the steel part that shields and strengthens the magnet, optimally concentrating the magnetic flux on the rubberized magnetic surface.

The rubber protects sensitive surfaces from being damaged by the magnet and also delivers a high friction coefficient, resulting in high lateral displacement forces.

- More information to retaining magnets (see page 2022)

TECHNICAL INFORMATION


- Elastomer characteristics (see page A32)

ACCESSORY


- Holding Disks GN 70 (see page 2051)
- Adhesive Disks GN 70.1 (see page 2051)

ON REQUEST

- Other colors
- Other shore hardnesses



View of magnetic surface



GN 51.5

Description	d1	d2	h	t1	t2	Nominal magnetic forces in N	⚖️
GN 51.5-ND-18-SW	18	M 4	6	3.5	0.8	25	6
GN 51.5-ND-22-SW	22	M 4	6	4.5	0.8	38	11
GN 51.5-ND-31-SW	31	M 5	6	4.5	0.8	89	21
GN 51.5-ND-43-SW	43	M 4	6	4	0.8	100	32
GN 51.5-ND-57-SW	57	M 5	7.5	4.5	1.2	200	79
GN 51.5-ND-66-SW	66	M 6	8.5	6	1.8	250	112
GN 51.5-ND-88-SW	88	M 6	8.5	6	1.8	550	186
GN 51.5-ND-18-WS	18	M 4	6	3.5	0.8	25	6
GN 51.5-ND-22-WS	22	M 4	6	4.5	0.8	38	11
GN 51.5-ND-31-WS	31	M 5	6	4.5	0.8	89	21
GN 51.5-ND-43-WS	43	M 4	6	4	0.8	100	32
GN 51.5-ND-57-WS	57	M 5	7.5	4.5	1.2	200	79
GN 51.5-ND-66-WS	66	M 6	8.5	6	1.8	250	112
GN 51.5-ND-88-WS	88	M 6	8.5	6	1.8	550	186